

### **ARTICULATED BOOM LIFT**

## XGA18ACK





# XGA18ACK Articulated boom lift



#### **FEATURES**

#### **MEASUREMENTS**

18m working height up to 256/350kg lift capacity

#### **PRODUCTIVITY**

1.83m x 0.76m working platform 256/350kg platform load capacity 160° platform rotation

4-wheel drive

2 steering wheels

30% theoretical gradeability

Horn

Solid rubber tires

Platform automatic leveling system

Fully proportional multi-function controls

Enable switch

Hourmeter record

Tilt alarm

Lift and lower alarm

Drive alarm

Lockable canopy

High/Slow speed mode


Flashing beacon

#### **POWER**

400Ah/48V Lead-acid batteries 1.9kW/12V DC emergency control unit 12V DC proportional control

#### **OPTIONS**

Axle balancing system
Turntable 360° continuous rotation
Platform working light
Tool tray
Non-marking tires
412Ah/51.2V Lithium batteries



Item	Unit	XGA18ACK
Working height	m	18
Platform height	m	16
Working radius	m	10.1
Lift capacity	kg	256/350
Occupant capacity	-	2
1st Boom luffing range	0	0~65
2nd Boom luffing range	0	-11~+75
Fly jib luffing range	0	-65~+70
Turntable rotation	0	355
Platform rotation	0	160
Drive Speed (retracted/extended)	km/h	4.8/0.6
Turning Radius (inside/outside)	m	3.2/4.7
Tailswing	mm	0
Ground clearance	mm	250
Gradeability	%	30
Tires	-	250-15/7.5
Control system	-	12V DC proportional control
Emergency control unit	kW∕V	1.9/12 DC
Batteries	V/Ah	48/400 Lead-acid (standard) 51.2/412 Lithium (optional)
Charger	V/A	48/35 Lead-acid (standard) 48/60 Lithium (optional)
Main power unit	kW/V	12/32
Dirve Motor	kW/V	3.3/32
Hydraulic tank	L	82
Weight	kg	8600
Platform size	mm	1830×760
a Length (transportation)	mm	7575/7550
b Width	mm	2320
c Height	mm	2350
d Wheelbase	mm	2360

SOLID TO SUCCEED